



## INSULATING and SEALING GEL



## RE-ENTERABLE



## RE-USABLE



# Magic Power Gel

The unique bi-component gel in a single bottle, with superior dielectric, sealing and thermal characteristics, re-enterable and re-usable!

- Very sticky
- Strong self amalgamating characteristics
- Single compact bottle; convenient twin compartment
- Re-usable as well as re-enterable, even after long working periods
- It doesn't give any waste
- Non toxic and safe





### Stickiness

- Exceptional sealing properties in any condition
- Better resistance to pressure
- Effective even in vertical or ceiling applications

### Self-agglomerating

- Once cross linked it perfectly adheres on itself characteristics to get an homogeneous and compact mass
- It can be therefore applied in multiple layers

### Zero waste


- Due to the nature of the product waste is eliminated; even residual product can be saved and used for the next application
- Also any left over product maintains it's high performance characteristics

### Single bottle

- Highly useful
- The most compact packaging
- Less space occupied in the toolbox
- Both components in the same packaging

## Magic Power Gel

Product	Colour	Package type	Quantity
Magic Power Gel	●	1 single, bi-component bottle 1 small basin - 1 mixing spoon	1000 ml
Magic Power Gel 500	●	1 single, bi-component bottle 1 small basin - 1 mixing spoon	500 ml
Magic Power Gel 250	●	1 single, bi-component bottle	250 ml



For all types of connections, even in the toughest conditions, for power, telecom and signalling!

Gel: UL 94-HB

**Dielectric strength:**

>23 kV/mm

**Cross linking time:**

fast (about 15 min. at 25°C)

**Volume resistivity:**

>2 . 10<sup>15</sup> Ω cm

**Operating temperature:**

-60°C / +200°C

**Overload temperature**

**for short periods:**

uo to 250°C

**Stabilised for:**

mould - UV

**Degree of protection:**

IP68 (in proper casings)

**IP68** | **IMQ**  
OFFICIALLY TESTED



Ray  
tech