

DECLARATION of PERFORMANCE

Number : **BR-103**

1. Unique identification code of the product:

H05V-K

Diameter: From : 1.9 To: 2.4

Number of conductors: 1

Conductor section (mm²): 0.5 - 0.75 - 1

2. Intended use of the product :

It is used as surface mounted or flush mounted in stationary plants, dry places, distribution boards and closed spaces factories, workshops and any kind of workplaces.

3. Manufacturer:

**BORSAN Kablo Elektrik Aydınlatma İnş. ve Tic. A.Ş Şabanolu OSB Mah. Organize Sanayi Bulv. No:40/1
Tekkeköy/Samsun / TURKEY**

4. System of assessment and verification of constancy of performance of the product

System 3

**The range of cables described in 1&2 belongs to Euroclass Eca
Euroclass Eca equals to System 3**

5. Notified Body:

NR 2659

Test Report Number: ISSep - Nr 2786/2017

6. Declared Performance

Essential characteristics	Performance	Harmonized Technical Specification
Reaction to fire	Eca	EN 50575:2014/A1:2016
Dangerous substances	None	

7. The performance of the product defined is suitable for the performance declared in Article 6.

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and in name of the manufacturer by:

Product Development Manager:

Borsan Kablo Elektrik Aydınlatma Aş.

Bakır Fabrika/Copper Factory

OSB Organize Sanayi Bulvarı
No: 40-1
Tekkeköy / Samsun

T: +90 (362) 266 5925

F: +90 (362) 266 6194

E-mail: borsan@borsan.com.tr

E-posta: export@borsan.com.tr

Alüminyum Fabrika/Aluminum Factory

OSB Vali M. Erdoğan Cebeci Bulvarı No: 54
Tekkeköy / Samsun

T: +90 (362) 266 9914

F: +90 (362) 266 9989

E-mail: borsan@borsan.com.tr

E-posta: export@borsan.com.tr

İbrahim KILIÇ
26.06.2017

BORSAN KABLO ELEKTRİK
AYDINLATMA İNŞ. VE TİC. A.Ş.
SAMSUN İLİ, SAMSUN İLİ, S.Ş.
T.C. İÇİŞİLERİ BAKANLIĞI
T.C. İÇİŞİLERİ BAKANLIĞI
T.C. İÇİŞİLERİ BAKANLIĞI