

Produktark

**BETAtherm®**  
**Halogenfri enleder**



BETAtherm® er en halogenfri enleder med fortinnet leder.



Temperaturklasse: F(155°C)  
Isolasjon: Polyolefin copolymer  
Nominellspenning: 600V  
Gjennomslagsfasthet: 3500V

El.Nr	Varetekst	Forpakning	Diameter
K1300025	BETATHERM 155 0,25mm SORT	200 m/rull	1,55 mm
K1300050	BETATHERM 155 0,50mm SORT	200 m/rull	1,90 mm
K1300075	BETATHERM 155 0,75mm SORT	200 m/rull	2,2 mm
K1300100	BETATHERM 155 1,00mm SORT	100 m/rull	2,45 mm
K1300150	BETATHERM 155 1,50mm SORT	100 m/rull	3 mm
K1300250	BETATHERM 155 2,50mm SORT	100 m/rull	3,65 mm
K1300400	BETATHERM 155 4,00mm SORT	100 m/rull	4,2 mm
K1300600	BETATHERM 155 6,00mm SORT	100 m/rull	4,8 mm
K1301000	BETATHERM 155 10,00mm SORT	100 m/rull	6,3 mm
K1301600	BETATHERM 155 16,00mm SORT	50 m/rull	7,3 mm
K1302500	BETATHERM 155 25,00mm SORT	50 m/rull	9,6 mm
K1303500	BETATHERM 155 35,00mm SORT	25 m/rull	10,7 mm
K1305000	BETATHERM 155 50,00mm SORT	25 m/rull	13 mm
K1307000	BETATHERM 155 70,00mm SORT	25 m/rull	15 mm
K1309500	BETATHERM 155 95,00mm SORT	25 m/rull	17,3 mm

**ELIS ELEKTRO AS**

Jerikoveien 16, 1067 Oslo  
Telefon: 22 90 56 70

post@eliselektro.no  
www.eliselektro.no

