

Produktark

Blindpropp



For å blinde nippel og samtidig ivareta kravet til IP68, når kabel skal monteres senere.



Materiale: Polyetylen
Temperaturbestandighet: -40 °C til +80 °C
Halogenfri: Ja

El.Nr	Varetekst	Diameter bunnDiameter topp	
1252650	Blindpropp PG7/M12 Ø:6mm	6 mm	8 mm
1252651	Blindpropp PG9/M16 Ø:8mm	8 mm	12 mm
1252652	Blindpropp PG11/M16 Ø:10mm	10 mm	16 mm
1252653	Blindpropp PG13/M20 Ø:12mm	12 mm	18 mm
1252654	Blindpropp PG16/M20 Ø:14mm	14 mm	20 mm
1252655	Blindpropp PG21/M25 Ø:17mm	17 mm	20 mm
1252656	Blindpropp PG29/M32 Ø:24mm	24 mm	28 mm
1252657	Blindpropp PG36/M40 Ø:30mm	30 mm	33 mm
1252658	Blindpropp PG42/M50 Ø:39mm	39 mm	47 mm
1252659	Blindpropp PG48/M63 Ø:45mm	45 mm	50 mm

ELIS ELEKTRO AS

Jerikoveien 16, 1067 Oslo
Telefon: 22 90 56 70

post@eliselektro.no
www.eliselektro.no

